

# Aimpoint® **CompC3**

Specifically designed to be used whenever you need a compact sight, Aimpoint's CompC3 is the shortest and lightest sight in Aimpoint's product range. This sight is perfect for those who don't want to carry any extra weight. This is the natural choice if you are able or want to use only a 1- ring mount. This sight can be used on most types of firearms and like most Aimpoint sights, the CompC3 works under all weather conditions, from the polar ice caps to the tropics.



## **Unique features of the CompC3**

- Ideal for most rifles, bows and competition pistols
- Easy to mount, equipped with a 30 mm wide ring that fits all Weaver bases
- New ACET technology allows 50,000 hours of operation on one battery
- Available in 2 dot sizes (2 and 4 MOA)
- Submersible to 15 feet (5 meters)
- Also available in a fixed 2X version

## **Standard features on all Aimpoint sights**

- Unlimited field of view
- Parallax-free. No centering required
- Unaffected by sub-zero temperatures
- Rugged, durable construction
- No hazardous materials
- No laser diode that could be harmful to your eyes
- Mechanical switch for speed and reliability
- Increased aiming confidence



**THE FUTURE IN SIGHT™**

**APPLICATION AREAS**

Hunters Primary use  
 IPSC shooters Primary use (CompC3)

**APPLICATION FIREARMS**

Pistol - Revolver Primary use  
 Bow Primary use  
 Scout rifle Primary use  
 Combination rifle Primary use  
 Drilling Primary use  
 Magnum handgun Secondary use  
 Semi-automatic rifle Secondary use  
 Rifle with shorter action Secondary use  
 Rifle with standard length action Secondary use

**TECHNOLOGY**

ACET Advanced Circuit Efficiency Technology

**OPTICAL DATA**

Reflex collimator sight Red dot sight  
 LED (Light Emitting Diode) Totally eye-safe  
 Red dot size 4 MOA\* (CompC3)  
 2 MOA\* (CompC3) (CompC3 2X)  
 1 MOA\* (CompC3 2X)  
 Parallax-free No centering required  
 Eye relief Unlimited  
 Anti-reflex coating All surfaces & multi-layer coating  
 Magnification 1X (CompC3)  
 Fixed 2X power attachment (CompC3 2X)

**ELECTRONIC DATA**

Battery One 3V Lithium battery, type 2L76 or DL1/3N  
 Battery life 50,000 hours  
 Mechanical switch Dot intensity regulator, 10 settings  
 Settings 1Off, 9 daylight

**MECHANICAL DATA**

Material housing Extruded aircraft aluminum  
 Surface finish Anodised, semi-matte  
 Color Carbon black  
 Adjustment 1 click = 13mm at 100 meters = 1/2" at 100 yards  
 Mounting solution 1 ring, 30 mm Ø

**ENVIRONMENTAL DATA**

Temperature range -30°– +60° C, -20° – +140° F  
 Water resistance Submersible to 15 ft, 5 m  
 Radioactive components used None

**DIMENSIONS**

Length 125 mm, 4.9" (CompC3) 160 mm, 6.1" (CompC3 2X)  
 Width/height 55 mm, 2.2" (CompC3) 58 mm, 9.5" (CompC3 2X)  
 Maximum ring width 30 mm  
 Weight 200 g, 7,1 oz (CompC3) 270 g, 9,5 oz (CompC3 2X)

**ARTICLE NUMBERS**

4 MOA 11402 (CompC3)  
 2 MOA 11421 (CompC3), 11412 (CompC3 2X)  
 1 MOA 11422 (CompC3 2X)



M00480

\* MOA (minute of angle) 1 MOA = 30 mm at 100 meters = 1" at 100 yards