

AIMPOINT® MICRO H-2 WITH MOUNT FOR LEUPOLD QR



AIMPOINT® MICRO H-2 WITH MOUNT FOR LEUPOLD QR

Item No.	200220
Aiming dot size	2 MOA
Battery type	3V lithium battery, type CR2032
Battery life - Day time use	50 000h (over 5 years of continuous use)

OVERVIEW

The Aimpoint® Micro H-2 is now available to the well known and popular Quick Release (QR) mount from Leupold.

The Aimpoint® Micro H-2 (2MOA) sight and the Leupold QR mount are sold as a kit with Item No. 200220. The mount is also available **separately**, Item No. 200224.

Launched 2015.

AIMPOINT® MICRO H-2 WITH INTEGRATED LEUPOLD QR MOUNT

The Leupold QR mount uses both anchor points of the Leupold base, for an ideal stability and function. The quick mounting using two levers, makes it possible to swiftly dismount and remount without the accuracy being affected. The Aimpoint® Leupold QR mount fits most action lengths on the market since it is adjustable to fit anchor points positioned between 90 mm – 135 mm (3.5 in – 5.3 in) apart.

To mount or to remove the Aimpoint® Micro Mount for Leupold QR base you use the "normal" leavers on the side of the Leupold base. The Leupold QR mount fits both Aimpoint® Micro H-1 and H-2, but only Micro H-2 is sold as a kit with a factory installed mount.

AIMPOINT® MICRO H-2

The extremely compact Micro H-2 offers up to five years of constant on power from a single CR-2032 battery, and has 12 brightness settings for optimal performance in any light conditions. This sight is completely waterproof, and is a result of feedback coming from hard core customers desiring an even more hard core Micro sight. With a redesigned and reinforced house body, as well as flip-up covers protecting the lenses, the Micro H-2 can withstand all types of environmental conditions. And thanks to new optical lenses and cutting edge lens coatings, the optical performance and the shape and clarity of the red dot are radically improved.

AIMPOINT® MICRO H-2 WITH MOUNT FOR LEUPOLD QR

TECHNICAL SPECIFICATIONS

GENERAL SPECIFICATIONS	POWER SOURCE	ENVIRONMENTAL SPECIFICATIONS
Item No.: 200220	Battery type: 3V lithium battery, type CR2032	Temperature range operation: -30°C to +60°C (-20°F to +140°F)
OPTICAL SPECIFICATIONS	Battery life - Day time use: 50 000h (over 5 years of continuous use)	Temperature range storage: -51°C to +71°C (-60°F to +160°F)
Operating principle: Reflex collimator sight with LED	Power intensity: 1 Off position and 12 daylight settings	Submersible: To a depth of 5 m (15 ft)
Optical magnification: 1x	PHYSICAL SPECIFICATIONS	
Aiming dot size: 2 MOA	Length sight only: 68 mm (2.7 in)	
Dot intensity: Visible against a background luminance of 0.1 to 55 000 lx	Length conf: 150 mm (5.9 in)	
Dot color: Peak Wavelength: 655 ± 15 nm	Width sight only: 41 mm (1.6 in)	
NVD compatible: No	Height sight only: 36 mm (1.4 in)	
Optical coating: Anti-reflex, all surfaces and multi-layer.	Height conf: 45 mm (1.75 in)	
Clear aperture: 18 mm (.71 in)	Weight sight only (incl battery): 94 g (3.3 oz)	
Eye relief: Unlimited	Weight conf: 150 g (5.3 oz) incl mount	
	Housing material: High strength aluminum	
	Housing finish and color: Semi-matte black	
	Housing anodized: Yes	
	Material mount and spacer std conf: Aluminum	
	Material lens cover: Thermoplastic Elastomer (TPE)	
	Surface treatment: Anodized, semi-matte	
	Adjustment: Range ±1 m at 100 meters (±1 yds at 100 yds) in windage and elevation, 1 click = 13 mm at 100 meters = 10 mm at 80 meters = .44 in at 100 yds	