



CompM2™

4 MOA - Red Dot Reflex Sight

- 4 MOA dot size
- 10,000 hours of constant operation
- 4 night vision compatible settings and 6 daylight settings
- Weight 200 g (7.1 oz) sight only
- Submersible to 25 meters (80 feet)
- Mounted with one wide 30 mm ring, or Aimpoint QR Ring
- This optic is the standard sight for the U.S. Army, the U.S. Air Force, and the armed forces of many NATO countries, known as M68/CCO (when used by U.S. forces).

INCLUDES: Flip-up Lens Covers, DL1/3N Battery

ITEM NO. 10336

PRODUCT

OVERVIEW

First introduced in 2000, nearly 300,000 Aimpoint® CompM2 sights are used by many Armed Forces including elite Special Forces worldwide.

The CompM2, also known as the M68/CCO (when used by U.S. forces), is the standard sight for the U.S. Army, the U.S. Air Force, and the armed forces of many NATO countries. The CompM2 is ready for use around the clock due to its compatibility with all generations of night vision devices (NVD). When the CompM2 was released, it became the benchmark against which all other combat optics are measured. While primarily utilized by armed forces, the CompM2 is also available to hunters and sport shooters who want a professional-grade sight. Holds up under the roughest physical handling and can withstand the most severe weather conditions and temperatures. Completely submersible and will withstand pressures up to 2.5 atmospheres allowing it to be taken up to 80 feet (25 meters) under water.

⊗ This product is no longer manufactured.

Service is still provided.

Launched: 2000 Discontinued: 2012

TECHNICAL

SPECIFICATIONS

PHYSICAL SPECIFICATIONS

Color Housing Black

Lens Covers Flip-up Lens Covers, Solid

Adjustment 1 Click = 16 mm at 100 m / 0.6 in at 100 yds

Tube Diameter 30 mm / 1.2 in

Material Lens Covers Thermoplastic Elastomer (TPE) / Chloroprene Rubber

OPTICAL SPECIFICATIONS

Dot Size 4 MOA

Night Vision Device (NVD) Compatible Yes

Eye Relief Unlimited

Dot Color Red

Optical Coating Anti-reflex coating all surfaces and multilayer coating objective lens

Parallax Operationally parallax free – No centering required

Magnification 1X - No Magnification

Transmission Average 60% in the range 420 - 700 nm

Diode LED (Light Emitting Diode) totally eye safe

Light Source Wavelength 650 nm red light

Clear Aperature 23 mm / 0.9 in

POWER SOURCE SPECIFICATIONS

Battery Life 10,000 h

Battery Quantity 1

Night Vision Device (NVD) Settings 4

Battery Type 1/3N, 3V, Lithium

Power Switch Rotary Switch

Daylight (DL) Settings 6

MOUNTING SPECIFICATIONS

Mounting Solution Not Included

TECHNOLOGY SPECIFICATIONS

Operating Principle Reflex collimator sight - red dot sight

ENVIRONMENTAL SPECIFICATIONS

Submersible to 25 m / 80 ft