



## CompML2™

### 4 MOA - Red Dot Reflex Sight

- 4 MOA dot size
- 10,000 hours of constant operation
- 9 daylight settings of which 1 extra bright
- Weight 200 g (7.1 oz) sight only
- Submersible to 25 meters (80 feet)
- Mounted with one wide 30 mm ring, or Aimpoint QR Ring
- The CompML2 is every bit as durable as the CompM2 and can withstand the roughest physical handling and extreme temperatures and weather conditions.

INCLUDES: Flip-up Lens Covers, DL1/3N Battery

ITEM NO. 10338

## PRODUCT OVERVIEW

The Aimpoint® CompML2 is a specially modified version of our groundbreaking CompC sight and is designed to meet law enforcement and military needs.

The CompML2 is every bit as durable as the CompM2 and can withstand the roughest physical handling and extreme temperatures and weather conditions. The very efficient CET technology diode gives the user months of continuous use on a single battery. The CompML2 is primarily designed for use in daylight and in low light conditions. The CompML2 can also be used by hunters and sport shooters who demand the best in the field. Note: For night vision compatibility, check out the CompM2.

⊗ This product is no longer manufactured.

Service is still provided.

Launched: 2000 Discontinued: 2010

## TECHNICAL SPECIFICATIONS

### OPTICAL SPECIFICATIONS

**Dot Size** 4 MOA

**Night Vision Device (NVD) Compatible** No

**Eye Relief** Unlimited

**Dot Color** Red

**Optical Coating** Anti-reflex coating all surfaces and multilayer coating objective lens

**Parallax** Operationally parallax free – No centering required

**Magnification** 1X – No Magnification

**Transmission** Average 60% in the range 420 – 700 nm

**Diode** LED (Light Emitting Diode) totally eye safe

**Light Source Wavelength** 650 nm Red Light, Peak: 655 ± 15 nm

**Clear Aperature** 23 mm / 0.9 in

### POWER SOURCE SPECIFICATIONS

**Battery Life** 10,000 h

**Battery Quantity** 1

**Daylight (DL) Settings** 9

**Battery Type** 1/3N, 3V, Lithium

**Power Switch** Rotary Switch

### PHYSICAL SPECIFICATIONS

**Color Housing** Black

**Lens Covers** Flip-up Lens Covers, Solid

**Adjustment 1 Click** = 16 mm at 100 m / 0.6 in at 100 yds

**Tube Diameter** 30 mm / 1.2 in

**Material Lens Covers** Thermoplastic Elastomer (TPE) / Chloroprene Rubber

### MOUNTING SPECIFICATIONS

**Mounting Solution** Not Included

### TECHNOLOGY SPECIFICATIONS

**Operating Principle** Reflex collimator sight - red dot sight