



Micro H-2™ 2 MOA

Red Dot Reflex Sight

with Mount for Sako Optilock

- 2 MOA dot size
- 50,000 hours (over 5 years) of operation on one battery
- 12 intensity settings for use in daylight and low light conditions
- Lightweight – 94 g (3.3 oz) sight only and 158 g (5.6 oz) with mount
- Submersible to 5 meters (15 feet)
- Advanced optical lenses for enhanced light transmission and ultimate dot clarity

INCLUDES: Micro™ Mount for Sako Optilock, Flip-up Lens Covers, CR2032 Battery, Aimpoint® Tool

ITEM NO. 200222

PRODUCT

OVERVIEW

Being the top choice for speed and accuracy in a compact reflex optic, the Aimpoint® Micro H-2 is trusted by millions of hunters and sport shooters worldwide.

This second generation Aimpoint® Micro red dot sight has a redesigned and reinforced house body, as well as flip-up covers protecting the lenses. Thanks to superior optical lenses and cutting edge lens coatings, the optical performance and the shape and clarity of the red dot are radically improved. This Aimpoint® Micro H-2 sight includes an integrated SAKO Optilock Mount. It is a quick release mount for the Sako 85 platform. The SAKO Optilock mount is attached to the front anchor point and is stably mounted, making dismount and remount possible, without the aiming accuracy being affected. This sight offers 50,000 hours of operation on a single battery.

⊗ This product is no longer manufactured.

Service is still provided.

Launched: 2015 Discontinued: 2017

TECHNICAL

SPECIFICATIONS

PHYSICAL SPECIFICATIONS

Size L x W x H - Sight Only 68 x 41 x 37 mm

Weight - Sight Only 94 g

Color Housing Black

Material Lens Covers Thermoplastic Elastomer (TPE)

Size L x W x H - Sight Only 2.7 x 1.6 x 1.5 in

Weight - Sight Only 3.3 oz

Lens Covers Flip-up Lens Covers, Transparent

Adjustment 1 Click = 13 mm at 100 m / 0.5 in at 100 yds

OPTICAL SPECIFICATIONS

Dot Size 2 MOA

Night Vision Device (NVD) Compatible No

Eye Relief Unlimited

Dot Color Red

Optical Coating Anti-reflex coating all surfaces and multilayer coating objective lens

Parallax Operationally parallax free – No centering required

Magnification 1X - No Magnification

Transmission Average 60% in the range 420 - 700 nm

Diode LED (Light Emitting Diode) totally eye safe

Light Source Wavelength 650 nm red light

Clear Aperture 18 mm / 0.7 in

POWER SOURCE SPECIFICATIONS

Battery Life 50,000 h at daylight setting 8 (15,000 Lux, room temperature)

Battery Quantity 1

Daylight (DL) Settings 12

Battery Type CR2032, 3V, Lithium

Power Switch Rotary Switch

MOUNTING SPECIFICATIONS

Mounting Solution Micro™ Mount for Sako Optilock

TECHNOLOGY SPECIFICATIONS

Operating Principle Reflex collimator sight - red dot sight

ENVIRONMENTAL SPECIFICATIONS

Submersible to 5 m / 15 ft

Radioactive Material None

Temperature Range Storage - 51°C to + 71°C / - 60°F to + 160°F

Laser None

Temperature Range Operation - 30°C to + 60°C / - 20°F to + 140°F

