



## 3X-C™

**Magnifier**  
with TwistMount™ Ring & Base

- Variable (-2 to +2) dioptic setting
- Compatible with Aimpoint red dot sights for longer range aiming or observation
- Ergonomic design for sure grip when used as a handheld observation tool; Shockproof
- Weight 220 g (7.8 oz) magnifier only
- Submersible to 0,5 meters (2 feet)
- Height of Optical Axis 30 mm (1.2 in) measured from top surface of mechanical interface
- No re-zeroing needed when shifting between non-magnified and magnified aiming

INCLUDES: TwistMount™, Allen Key

ITEM NO. 200343

## PRODUCT

### OVERVIEW

The Aimpoint® 3X-C offers 3X magnification and incorporates proven design features and premium Aimpoint quality at an entry level price point.

The 3X-C can also be used as a handheld 3X monocular. These magnifiers utilize the red dot in sights as the aiming reticle, eliminating the need for re-zeroing when shifting between non-magnified and magnified aiming. A variable (-2 to +2) dioptic setting allows this magnifier to be adapted to the individual shooter's eye. The 3X-C is encased in a shock absorbing protective rubber cover that also creates an ideal ergonomic grip. Internal optical adjustments make aligning the magnifier and sight quick and easy. This model includes a TwistMount base.

The 3X-C magnifier is optimized for use with the Micro T-2/H-2, CompM4 Series, and CompM5 series of sights for long-range aiming or observation provides a crisp sight picture with a generous field of view.

Launched: 2016

## KEY

### FEATURES

- 3X optical magnification
- Also serves as a handheld 3X monocular
- No re-zeroing needed when shifting between non-magnified and magnified aiming – utilizes the red dot in Aimpoint sights as the aiming reticle
- Field of view (FOV): 6°
- Including a TwistMount Base
- Legendary Aimpoint ruggedness at an entry level price point

## TECHNICAL

# SPECIFICATIONS

### MOUNTING SPECIFICATIONS

**Mounting Solution** TwistMount™ Ring & Base

### ENVIRONMENTAL SPECIFICATIONS

**Submersible to** 0.5 m / 2 ft

**Radioactive Material** None

**Temperature Range Storage** - 35°C to + 55°C / - 31°F to + 131°F

**Humidity - Operable during and after Humidity. Limits:** Operable during and after Humidity. Limits: RH: 95%, Temp: +20°C to +50°C (+68°F to +122°F), cyclic

**Vibration - Withstands vibration. Limits:** Withstands Vibration. Limits: Vibration, sinusoidal in a frequency range of 10-150 Hz. Frequency: 10-30 Hz, ±1.587 mm, Frequency: 30-150 Hz. 5.75 g, 1 octave/min. Direction: X, Y and Z, Time: 30 min/direction.

**Laser** None

**Temperature Range Operation** - 35°C to + 55°C / - 31°F to + 131°F

**Temperature Shock** Operable after a temperature shock between - 25°C and + 40°C / - 13°F and + 104°F

**Shock - Operable before and after shock. Limits:** Operable before and after shock. Limits: X-axis: 500 g, 0.7 – 1.1 ms (3 shocks), Y-axis: 40g ±4g, 11 ±1ms (2 shocks in each direction, Z-axis: 40g ±4g, 11 ±1ms, 2 shocks in each direction.

### PHYSICAL SPECIFICATIONS

**Size L x W x H** 103 x 49 x 60 mm

**Weight -**

**Size L x W x H - Sight Only** 103 x 45 x 45 mm

**Weight - Sight Only** 220 g

**Material Housing and Tube** Aluminum

**Color Housing** Matte Grey to Black

**Lens Covers** Not Included

**Height of Optical Axis** 30 mm / 1.2 in measured from top surface of mounting platform

**Size L x W x H** 4.1 x 1.9 x 2.4 in

**Weight -**

**Size L x W x H - Sight Only** 4.1 x 1.8 x 1.8 in

**Weight - Sight Only** 7.8 oz

**Surface Finish Housing** Protective Rubber Cover

**Tube Diameter** 30 mm / 1.2 in

**Material Mounting Solution** Aluminum

### OPTICAL SPECIFICATIONS

**Magnification** 3X

**Night Vision Device (NVD) Compatible** Yes

**Field of View (FoV°)** 6°

**Dioptric Adjustment** ± 2.0 D

**Eye Relief** 56 mm / 2.2 in

**Exit Pupil** 6.5 mm / 0.25 in