



CompC3™

2 MOA - Red Dot Reflex Sight
with Mount for Semi-Automatic Rifles

- 2 MOA dot size
- 50,000 hours (over 5 years) of constant operation on one battery
- 9 position rotary intensity adjustment
- Weight 200 g (7.1 oz) sight only
- Submersible to 5 meters (15 feet)
- Height of Optical Axis 25 mm (1.0 in) measured from top surface of mechanical interface
- Ideal for use on rifles with short to standard actions, shotguns, semi-automatic rifles, and crossbows

INCLUDES: CompC3™ Mount for Semi-Automatic Rifles,
DL1/3N Battery, Allen Key

ITEM NO. 200245

PRODUCT OVERVIEW

Aimpoint® CompC3 is the lightest sight in its class and is specifically designed to use whenever you need a compact sight with a 30 mm tube.

The Aimpoint CompC3 is designed to be used whenever you need a compact sight with a 30 mm tube diameter. This sight has a precise 2 MOA dot and is a member of the Comp series sights - recognized leader for the professional market. This CompC3 model comes with a mount for semi-automatic rifles (Browning Bar, Maral, Winchester SXR, Benelli ARGO) is attached directly to the action.

The Aimpoint CompC3 is a compact sight with the same high quality and performance as sights for the professional market.

Launched: 2016

KEY FEATURES

- Anodized high strength aluminum housing, semi-matte black
- The civilian version of the rugged Aimpoint Comp-series that is first to meet the requirement of MIL-SPEC

TECHNICAL

SPECIFICATIONS

PHYSICAL SPECIFICATIONS

Weight 277 g

Size L x W x H - Sight Only 120 x 48 x 48 mm

Weight - Sight Only 200 g

Material Housing and Tube High Strength Aluminum

Color Housing Black

Lens Covers Bikini Lens Cover, Rubberband

Height of Optical Axis 25 mm / 1.0 in measured from top surface of mounting platform

Weight 9.8 oz

Size L x W x H - Sight Only 4.7 x 1.9 x 1.9 in

Weight - Sight Only 7.1 oz

Surface Finish Housing Anodized, Semi-Matte

Tube Diameter 30 mm / 1.2 in

Material Mounting Solution Aluminum

Adjustment 1 Click = 16 mm at 100 m / 0.6 in at 100 yds

OPTICAL SPECIFICATIONS

Dot Size 2 MOA

Magnification 1X - No Magnification

Transmission Average 60% in the range 420 - 700 nm

Diode LED (Light Emitting Diode) totally eye safe

Light Source Wavelength 650 nm red light

Parallax Operationally parallax free – No centering required

*** MOA (minute of angle)** 1 MOA \approx 30 mm at 100 meters \approx 1 in at 100 yards

Night Vision Device (NVD) Compatible No

Eye Relief Unlimited

Dot Color Peak Wavelength: 655 \pm 15 nm

Clear Aperature 23 mm / 0.9 in

POWER SOURCE SPECIFICATIONS

Battery Life 50,000 h at daylight setting 7 (15,000 Lux, room temperature)

Power Switch Rotary Switch

Battery Type 1/3N, 3V, Lithium

Daylight (DL) Settings 9

MOUNTING SPECIFICATIONS

Mounting Solution CompC3™ Mount for Semi-Automatic Rifles

Torque - Mount to Sight 1.5 Nm / 13 in-lbs

Mounting Platform Browning Bar / Maral / BLR, Winchester SXR, Benelli ARGO

TECHNOLOGY SPECIFICATIONS

Operating Principle Reflex collimator sight - red dot sight

ENVIRONMENTAL SPECIFICATIONS

Aimpoint

5 m / 15 ft

Radioactive Material None

Temperature Range Storage - 51°C to + 71°C / - 60°F to + 160°F

Laser None

Temperature Range Operation - 30°C to + 60°C / - 20°F to + 140°F