

Micro H-1™

4 MOA - Red Dot Reflex Sight without Mount

- 4 MOA dot size
- 50,000 hours (over 5 years) of operation on one battery
- 12 intensity settings for use in daylight and low light conditions
- Lightweight – 84 g (3.0 oz) sight only
- Submersible to 5 meters (15 feet)

INCLUDES: Bikini Lens Covers, CR2032 Battery, Aimpoint® Tool

ITEM NO. 12526

PRODUCT OVERVIEW

The Aimpoint® Micro H-1 has become a very popular hunting sight worldwide due to its size, light weight and robust build quality.

Micro H-1 was designed with the hunter in mind. This small sight model is available in two MOA sizes; 2 and 4 MOA. It is rugged and reliable, for increased confidence in the harshest of elements.

The Aimpoint Micro H-1 is among the lightest red dot sights on the market and still tough enough to carry the Aimpoint name.

Launched: 2007

KEY FEATURES

- Available in 2 dot sizes (2, and 4 MOA)
- No mount included
- Operational in extreme weather conditions
- Extremely rugged, durable construction
- Anodized high strength aluminum housing, semi-matte black
- Precision adjustment for windage and elevation: top of protective caps fits into holes on adjustment screws – no other tool required

TECHNICAL

SPECIFICATIONS

PHYSICAL SPECIFICATIONS

Size L x W x H - Sight Only 61 x 41 x 36 mm

Weight - Sight Only 84 g

Material Housing and Tube High Strength Aluminum

Color Housing Black

Size L x W x H - Sight Only 2.4 x 1.6 x 1.4 in

Weight - Sight Only 3.0 oz

Surface Finish Housing Anodized, Semi-Matte

Adjustment 1 Click = 13 mm at 100 m / 0.5 in at 100 yds

OPTICAL SPECIFICATIONS

Dot Size 4 MOA

Night Vision Device (NVD) Compatible No

Eye Relief Unlimited

Dot Color Red

Optical Coating Anti-reflex coating all surfaces and multilayer coating objective lens

Parallax Operationally parallax free – No centering required

Magnification 1X - No Magnification

Transmission Average 60% in the range 420 - 700 nm

Diode LED (Light Emitting Diode) totally eye safe

Light Source Wavelength 650 nm red light

Clear Aperture 18 mm / 0.7 in

POWER SOURCE SPECIFICATIONS

Battery Life 50,000 h at daylight setting 8 (15,000 Lux, room temperature)

Battery Quantity 1

Power Switch Rotary Switch

Battery Type CR2032, 3V, Lithium

Battery Size CR2032

Daylight (DL) Settings 12

TECHNOLOGY SPECIFICATIONS

Operating Principle Reflex collimator sight - red dot sight

ENVIRONMENTAL SPECIFICATIONS

Submersible to 5 m / 15 ft

Radioactive Material None

Temperature Range Storage - 51°C to + 71°C / - 60°F to + 160°F

Laser No Laser Emission

Temperature Range Operation - 30°C to + 60°C / - 20°F to + 140°F