



Micro H-2™ Orange

2 MOA - Red Dot Reflex Sight

with Standard Mount for Weaver / Picatinny

- This sight model is a special edition and limited run with Orange Cerakote® H-Series surface coating
- 2 MOA dot size
- 50,000 hours (over 5 years) of operation on one battery
- 12 intensity settings for use in daylight and low light conditions
- Lightweight – 94 g (3.3 oz) sight only
- Submersible to 5 meters (15 feet)
- Advanced optical lenses for enhanced light transmission and ultimate dot clarity

INCLUDES: Micro™ Standard Mount, Flip-up Lens Covers, CR2032 Battery, Aimpoint® Tool

ITEM NO. 200715

PRODUCT

OVERVIEW

Being the top choice for speed and accuracy in a compact reflex optic, the Aimpoint® Micro H-2 is trusted by millions of hunters and sport shooters worldwide.

This second generation Aimpoint® Micro red dot sight has a redesigned and reinforced house body, as well as flip-up covers protecting the lenses. Thanks to superior optical lenses and cutting edge lens coatings, the optical performance and the shape and clarity of the red dot are radically improved. It offers 50,000 hours of operation on a single battery.

This Special Edition of the Micro H-2 model is finished with an orange Cerakote® H-Series surface coating - an advanced thin-film ceramic coating that bonds completely with the aluminum alloy housing of the sight. Cerakote® finishes are known worldwide for their corrosion and chemical resistance, UV and thermal stability, and durability under extreme conditions. .

Micro H-2 combines simplicity, speed, ruggedness, accuracy and reliability.

Launched: 2020

KEY

FEATURES

- Limited run edition with an Orange Cerakote® H-Series surface coating
- Front and rear transparent lens caps included
- Reinforced turret protection for even greater ruggednessCompatible with all Aimpoint Magnifiers
- Operational in extreme weather conditions
- Anodized high strength aluminum housing, semi-matte black
- Extremely rugged, durable construction

TECHNICAL

SPECIFICATIONS

PHYSICAL SPECIFICATIONS

Size L x W x H 79 x 45 x 48 mm

Weight 130 g

Size L x W x H - Sight Only 68 x 41 x 36 mm

Weight - Sight Only 94 g

Material Housing and Tube High Strength Aluminum

Color Housing Orange

Material Lens Covers Thermoplastic Elastomer (TPE)

Height of Optical Axis 20 mm / 0.8 in measured from top surface of mounting platform

Size L x W x H 3.1 x 1.8 x 1.9 in

Weight 4.6 oz

Size L x W x H - Sight Only 2.7 x 1.6 x 1.4 in

Weight - Sight Only 3.3 oz

Surface Finish Housing Cerakote® H-Series surface coating

Lens Covers Flip-up Lens Covers, Transparent

Material Mounting Solution Aluminum

Adjustment 1 Click = 13 mm at 100 m / 0.5 in at 100 yds

OPTICAL SPECIFICATIONS

Dot Size 2 MOA

Magnification 1X - No Magnification

Transmission Average 60% in the range 420 - 700 nm

Diode LED (Light Emitting Diode) totally eye safe

Light Source Wavelength 650 nm red light

Clear Aperature 18 mm / 0.7 in

*** MOA (minute of angle)** 1 MOA \approx 30 mm at 100 meters \approx 1 in at 100 yards

Night Vision Device (NVD) Compatible No

Eye Relief Unlimited

Dot Color Red

Optical Coating Anti-reflex coating all surfaces and multilayer coating objective lens

Parallax Operationally parallax free – No centering required

POWER SOURCE SPECIFICATIONS

Battery Life 50,000 h at daylight setting 8 (15,000 Lux, room temperature)

Battery Quantity 1

Power Switch Rotary Switch

Battery Type CR2032, 3V, Lithium

Battery Size CR2032

Daylight (DL) Settings 12

MOUNTING SPECIFICATIONS

Mounting Solution Micro™ Standard Mount for Weaver / Picatinny

Torque - Mount to Sight 1.35 Nm / 12 in-lbs (Torx T10)

Mounting Platform Weaver / Picatinny Rail

Torque - Mount to Rail 2.0 Nm / 18 in-lbs (Torx T10)

TECHNOLOGY SPECIFICATIONS

Operating Principle Reflex collimator sight - red dot sight

ENVIRONMENTAL SPECIFICATIONS

Submersible to 5 m / 15 ft

Radioactive Material None

Temperature Range Storage - 51°C to + 71°C / - 60°F to + 160°F

Laser No Laser Emission

Temperature Range Operation - 30°C to + 60°C / - 20°F to + 140°F